


Ready To Go LEDLiner40

Down - Trimless



Average weight of equipped profile: 3.30 kg/m



Opal cover is standard. Prismatic cover is not available for LEDLiner40.

Included

- Carrier Profile
- Inner profile
- End Caps
- LED Modules
- PC Cover down
- Trimless brackets

Extra options: p.274-275
Wiring information: p.276
Technical drawings: p.277

Article number	Total length incl. end caps	Connected profile lengths excl. end caps	LED Flux* (830)	LED Flux* (840)	LED Flux* (927)	LED Flux* (930)	LED Flux* (940)	Power Ra80*** (W)
R40TR. DM.CCC.xx -06	879 mm	-	3132 lm	3300 lm	3084 lm	3132 lm	3300 lm	18.6W
R40TR. DM.CCC.xx -07	1021 mm	-	3654 lm	3850 lm	n.a.**	3654 lm	3850 lm	21.7W
R40TR. DM.CCC.xx -08	1159 mm	-	4176 lm	4400 lm	4112 lm	4176 lm	4400 lm	24.8W
R40TR. DM.CCC.xx -09	1301 mm	-	4698 lm	4950 lm	n.a.**	4698 lm	4950 lm	27.9W
R40TR. DM.CCC.xx -10	1441 mm	-	5220 lm	5500 lm	5140 lm	5220 lm	5500 lm	31.0W
R40TR. DM.CCC.xx -11	1583 mm	-	5742 lm	6050 lm	n.a.**	5742 lm	6050 lm	34.1W
R40TR. DM.CCC.xx -12	1721 mm	-	6264 lm	6600 lm	6168 lm	6264 lm	6600 lm	37.2W
R40TR. DM.CCC.xx -13	1863 mm	-	6786 lm	7150 lm	n.a.**	6786 lm	7150 lm	40.3W
R40TR. DM.CCC.xx -14	2002 mm	-	7308 lm	7700 lm	7196 lm	7308 lm	7700 lm	43.4W
R40TR. DM.CCC.xx -15	2144 mm	-	7830 lm	8250 lm	n.a.**	7830 lm	8250 lm	46.5W
R40TR. DM.CCC.xx -16	2282 mm	-	8352 lm	8800 lm	8224 lm	8352 lm	8800 lm	49.6W
R40TR. DM.CCC.xx -17	2424 mm	-	8874 lm	9350 lm	n.a.**	8874 lm	9350 lm	52.7W
R40TR. DM.CCC.xx -18	2564 mm	-	9396 lm	9900 lm	9252 lm	9396 lm	9900 lm	55.8W
R40TR. DM.CCC.xx -19	2706 mm	-	9918 lm	10450 lm	n.a.**	9918 lm	10450 lm	58.9W
R40TR. DM.CCC.xx -20	2844 mm	-	10440 lm	11000 lm	10280 lm	10440 lm	11000 lm	62.0W
R40TR. DM.CCC.xx -21	2986 mm	-	10962 lm	11550 lm	n.a.**	10962 lm	11550 lm	65.1W
R40TR. DM.CCC.xx -22	3125 mm	-	11484 lm	12100 lm	11308 lm	11484 lm	12100 lm	68.2W
R40TR. DM.CCC.xx -23	3267 mm	-	12006 lm	12650 lm	n.a.**	12006 lm	12650 lm	71.3W
R40TR. DM.CCC.xx -24	3405 mm	-	12528 lm	13200 lm	12336 lm	12528 lm	13200 lm	74.4W
R40TR. DM.CCC.xx -25	3548 mm	1701 + 1843 mm	13050 lm	13750 lm	n.a.**	13050 lm	13750 lm	77.5W
R40TR. DM.CCC.xx -26	3687 mm	1701 + 1982 mm	13572 lm	14300 lm	13364 lm	13572 lm	14300 lm	80.6W
R40TR. DM.CCC.xx -27	3829 mm	1843 + 1982 mm	14094 lm	14850 lm	n.a.**	14094 lm	14850 lm	83.7W
R40TR. DM.CCC.xx -28	3968 mm	1982 + 1982 mm	14616 lm	15400 lm	14392 lm	14616 lm	15400 lm	86.8W
R40TR. DM.CCC.xx -29	4110 mm	1982 + 2125 mm	15138 lm	15950 lm	n.a.**	15138 lm	15950 lm	89.9W
R40TR. DM.CCC.xx -30	4248 mm	1982 + 2262 mm	15660 lm	16500 lm	15420 lm	15660 lm	16500 lm	93.0W
R40TR. DM.CCC.xx -31	4390 mm	2125 + 2262 mm	16182 lm	17050 lm	n.a.**	16182 lm	17050 lm	96.1W
R40TR. DM.CCC.xx -32	4528 mm	2262 + 2262 mm	16704 lm	17600 lm	16448 lm	16704 lm	17600 lm	99.2W
R40TR. DM.CCC.xx -33	4670 mm	2262 + 2405 mm	17226 lm	18150 lm	n.a.**	17226 lm	18150 lm	102.3W
R40TR. DM.CCC.xx -34	4810 mm	2262 + 2544 mm	17748 lm	18700 lm	17476 lm	17748 lm	18700 lm	105.4W
R40TR. DM.CCC.xx -35	4952 mm	2405 + 2544 mm	18270 lm	19250 lm	n.a.**	18270 lm	19250 lm	108.5W
R40TR. DM.CCC.xx -36	5091 mm	2544 + 2544 mm	18792 lm	19800 lm	18504 lm	18792 lm	19800 lm	111.6W
R40TR. DM.CCC.xx -37	5233 mm	2544 + 2686 mm	19314 lm	20350 lm	n.a.**	19314 lm	20350 lm	114.7W
R40TR. DM.CCC.xx -38	5371 mm	2544 + 2824 mm	19836 lm	20900 lm	19532 lm	19836 lm	20900 lm	117.8W
R40TR. DM.CCC.xx -39	5513 mm	2544 + 2966 mm	20358 lm	21450 lm	n.a.**	20358 lm	21450 lm	120.9W
R40TR. DM.CCC.xx -40	5653 mm	2544 + 3105 mm	20880 lm	22000 lm	20560 lm	20880 lm	22000 lm	124.0W
R40TR. DM.CCC.xx -41	5795 mm	2544 + 3248 mm	21402 lm	22550 lm	n.a.**	21402 lm	22550 lm	127.1W
R40TR. DM.CCC.xx -42	5933 mm	2824 + 3105 mm	21924 lm	23100 lm	21588 lm	21924 lm	23100 lm	130.2W
R40TR. DM.CCC.xx -43	6075 mm	2966 + 3105 mm	22446 lm	23650 lm	n.a.**	22446 lm	23650 lm	133.3W
R40TR. DM.CCC.xx -44	6214 mm	3105 + 3105 mm	22968 lm	24200 lm	22616 lm	22968 lm	24200 lm	136.4W
R40TR. DM.CCC.xx -45	6356 mm	3105 + 3248 mm	23490 lm	24750 lm	n.a.**	23490 lm	24750 lm	139.5W
R40TR. DM.CCC.xx -46	6494 mm	3105 + 3385 mm	24012 lm	25300 lm	23644 lm	24012 lm	25300 lm	142.6W
R40TR. DM.CCC.xx -47	6636 mm	3248 + 3385 mm	24534 lm	25850 lm	n.a.**	24534 lm	25850 lm	145.7W
R40TR. DM.CCC.xx -48	6774 mm	3385 + 3385 mm	25056 lm	26400 lm	24672 lm	25056 lm	26400 lm	148.8W

* The given flux is the luminous flux of the LED modules. To know the luminous flux of the luminaire, please apply the light output ratios on page 269.

** Not available. Our supplier, Philips, does not support 550lm LED modules Ra90-2700K.

*** Power consumption mentioned is for Ra80. Ra90 has a higher energy consumption. For detailed information, please check www.doxis.be

