



Tektus 60 Linear 1800mm

Technical Datasheet

DOXIS
LIGHTING FACTORY



General	
Type	Suspended luminaire
Material	Aluminium + Steel
Lamp Type	COB LED
Adjustable	Yes, Spots (60°/359°)
Dimmable	Yes
Cooling	Passive
Energy Class	A++
Weight	n.a.
Photobiol. Safety	RG1
Class	class I



IP20 960°C LED

Features:

High efficiency LED luminaire, equipped with a Bridgelux COB LED.
High quality components.
Various colors available.

Specifications


Art. nr.	Length	Lightsource INCLUDED	CCT - CRI	Light output* LED / System	Power** LED / System (current)	Power supply INCLUDED	SDCM
TEKTUS 60 Linear Down:							
1604.AA.24.927.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules	2700K - Ra90	Spots: (2x) 1517lm / 995lm Linear down: 4020lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W	Non dimmable driver 2 separate circuits***	3
1604.AA.24.930.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules	3000K - Ra90	Spots: (2x) 1577lm / 1035lm Linear down: 4160lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W	Non dimmable driver 2 separate circuits***	3
1604.AA.24.940.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules	4000K - Ra90	Spots: (2x) 1601lm / 1050lm Linear down: 4400lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W	Non dimmable driver 2 separate circuits***	3
1604.AA.26.927.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules	2700K - Ra90	Spots: (2x) 1517lm / 995lm Linear down: 4020lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W	Touch & DALI dim. driver 2 separate circuits***	3
1604.AA.26.930.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules	3000K - Ra90	Spots: (2x) 1577lm / 1035lm Linear down: 4160lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W	Touch & DALI dim. driver 2 separate circuits***	3
1604.AA.26.940.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules	4000K - Ra90	Spots: (2x) 1601lm / 1050lm Linear down: 4400lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W	Touch & DALI dim. driver 2 separate circuits***	3
TEKTUS 60 Linear Up&Down:							
1605.AA.24.927.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules Linear Up: Philips Fortimo LED Modules	2700K - Ra90	Spots: (2x) 1517lm / 995lm Linear down: 4020lm / n.a. Linear up: 4020lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W Linear up: 24.0W / 27.6W	Non dimmable driver 3 separate circuits***	3
1605.AA.24.930.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules Linear Up: Philips Fortimo LED Modules	3000K - Ra90	Spots: (2x) 1577lm / 1035lm Linear down: 4160lm / n.a. Linear up: 4160lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W Linear up: 24.0W / 27.6W	Non dimmable driver 3 separate circuits***	3
1605.AA.24.940.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules Linear Up: Philips Fortimo LED Modules	4000K - Ra90	Spots: (2x) 1601lm / 1050lm Linear down: 4400lm / n.a. Linear up: 4400lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W Linear up: 24.0W / 27.6W	Non dimmable driver 3 separate circuits***	3
1605.AA.26.927.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules Linear Up: Philips Fortimo LED Modules	2700K - Ra90	Spots: (2x) 1517lm / 995lm Linear down: 4020lm / n.a. Linear up: 4020lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W Linear up: 24.0W / 27.6W	Touch & DALI dim. driver 3 separate circuits***	3
1605.AA.26.930.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules Linear Up: Philips Fortimo LED Modules	3000K - Ra90	Spots: (2x) 1577lm / 1035lm Linear down: 4160lm / n.a. Linear up: 4160lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W Linear up: 24.0W / 27.6W	Touch & DALI dim. driver 3 separate circuits***	3
1605.AA.26.940.XX	1800mm	Spots: (2x) Citizen CLU038J LED Linear Down: Philips Fortimo LED Modules Linear Up: Philips Fortimo LED Modules	4000K - Ra90	Spots: (2x) 1601lm / 1050lm Linear down: 4400lm / n.a. Linear up: 4400lm / n.a.	Spots: (2x) 11.3W / 13.0W Linear down: 24.0W / 27.6W Linear up: 24.0W / 27.6W	Touch & DALI dim. driver 3 separate circuits***	3

0000.AA.00.000.XX

* LED light output represent values of LED modules. System light output incl. light losses of luminaire
** LED power values excl. driver. System power values incl. driver power consumption (driver efficiency of 87% used as reference)

- 23 - 23° Reflector - 0000.23.00.000.00
- 36 - 36° Reflector - 0000.36.00.000.00
- 48 - 48° Reflector - 0000.48.00.000.00
- 57 - 57° Reflector - 0000.57.00.000.00

Available colors - 0000.00.00.000.XX
Other RAL colors on request.



Detail of indirect (up) lighting:



*****Connection:**

- Non dim: 5-wire cable (L1, N, PE, L2, L3). Up, down and spots on separately switchable circuits with common N. If only 3 wires are available, L1, L2 and L3 can be connected together. Separate switching will not be possible.
- DALI: 5-wire cable (L, N, PE, DA1, DA2). Up, down and spots on three separate DALI channels.
- Touch dimmable ON REQUEST (L, N, PA, Touch L1, Touch L2, Touch L3) Up, down and spots on separate circuits with common N

