



A) Surface Mounted

1. Remove end cap and inside profile (disconnect wiring if required)
2. Pull power cable through provided hole
3. Fix profile to ceiling using screws
Only use pre-drilled holes
Respect screw dimensions
4. Connect 230V to inner profile
Reconnect wiring if required
5. Place inner profile back
Place end cap back

B) Suspended

6. Disassemble ceiling fixation
7. Fix ceiling fixation to ceiling using screws
8. Pull steel wire trough bottom part of ceiling fixation
9. Reassemble ceiling fixation
10. Remove end cap, inside profile and top cover (disconnect wiring if required)
11. Pull power cable through provided hole
12. Connect Power cable
Connect additional wiring if required
13. Place inner profile back
Place end cap back
14. Assemble suspension bracket
15. Insert suspension bracket into profile and place end caps back
Move bracket to desired location (>50mm from edge)
Fix bracket with set screw
(Bracket cannot be placed above connectors)
16. Put wire into wire locks
17. Adjust height so that profile is levelled

Connectors

18. Remove end cap and inside profile (disconnect wiring if required)
19. Slide brackets into the provided slots
Fix brackets with set screws (do not tighten too much, this can damage the profile)
20. Place end cap and inside profile back.
Reconnect wiring if required

⚠ Attention!!

Be very careful with LEDs when working on product! Do not touch LEDs. Do not let tools come in contact with LEDs. Warranty void if LED contact has taken place.

Only to be installed by a qualified electrician. Always make sure power is completely switched off when working on profile.

Always make sure suspension cables are placed perpendicular to both the ceiling and the profile itself.

When connecting multiple parts of a structure always make sure LED polarity is respected. This means connecting white to white and grey to grey wires.